

**Block Paving Sealant - Satin**

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 and SI 2020/1577

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 Product identifier**

Product Name Concrete Sealant - Matt
CAS No. Not applicable.
EC No. Not applicable.
Registration number(s) Not known.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Domestic, Commercial & Industrial use for concrete driveways, patios, paths & walkways, decorative, stamped, or pattern imprinted concrete.

Uses Advised Against Not known.

1.3 Details of the supplier of the safety data sheet

Manufacturer
Company Identification Multicrete Products Limited
Address of Manufacturer Units 1-2 Commerce Street
Carrs Industrial Estate
Haslingden
Rossendale
Lancashire
Postal code BB4 5JT
Telephone: 01706 212135
Fax 01706 217642
E-mail sales@multicreteproducts.co.uk
Office hours 08.30-16.30
Supplier

Company Identification Multicrete Products Limited
Address of Supplier Units 1-2 Commerce Street
Carrs Industrial Estate
Haslingden
Rossendale
Lancashire
Postal code BB4 5JT
Telephone: 01706 212135
Fax 01706 217642
E-mail sales@multicreteproducts.co.uk
Office hours 08.30-16.30

1.4 Emergency telephone number

Emergency Phone No. 01706 212135
Contact Christopher Barrientos
National response center
Address NHS Direct
Emergency Phone No. +44 111

SECTION 2: HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567
Flam. Liq. 3 :Flammable liquid and vapour.
Acute Tox. 4 :Harmful in contact with skin.
Skin Irrit. 2 :Causes skin irritation.
Acute Tox. 4 :Harmful if inhaled.

2.2 Label elements

According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567
Product Name Concrete Sealant - Matt

Hazard Pictogram(s)



GHS02



GHS07

**Block Paving Sealant - Satin**

Signal Word(s)	Warning
Hazard Statement(s)	H226: Flammable liquid and vapour. H312: Harmful in contact with skin. H315: Causes skin irritation. H332: Harmful if inhaled. EUH208: Contains: (methyl methacrylate, n-butyl methacrylate) May produce an allergic reaction.
Precautionary Statement(s)	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261: Avoid breathing vapours. P280: Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312: Call a POISON CENTER/doctor if you feel unwell.
2.3 Other hazards	None known.
2.4 Additional Information	For full text of H/P Statements see section 16.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Substances**

Not applicable.

3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / Registration number(s)	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Xylene	1330-20-7	215-535-7	75-85	Flam. Liq. 3 H226 Acute Tox. 4 H312 Skin Irrit. 2 H315 Acute Tox. 4 H332	GHS02 GHS07
silicon dioxide	7631-86-9	231-545-4	1-5	Not classified	None
n-butyl methacrylate	97-88-1	202-615-1	<1	Flam. Liq. 3 H226 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3 H335	GHS02 GHS07
methyl methacrylate	80-62-6	201-297-1	<1	Flam. Liq. 2 H225 Skin Irrit. 2 H315 Skin Sens. 1 H317 STOT SE 3 H335	GHS02 GHS07

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures**

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.



Block Paving Sealant - Satin

Skin Contact	Take off contaminated clothing and wash it before reuse. Rinse skin with water. If skin irritation occurs: Get medical advice/attention.
Eye Contact	Flush eyes with water for at least 15 minutes while holding eyelids open. If symptoms develop, obtain medical attention.
Ingestion	Treat symptomatically. Wash out mouth with water. If symptoms persist, obtain medical attention.
4.2 Most important symptoms and effects, both acute and delayed	Harmful in contact with skin or if inhaled Causes skin irritation.
4.3 Indication of any immediate medical attention and special treatment needed	Unlikely to be required but if necessary treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media	
Suitable Extinguishing media	Use water spray, foam, dry powder or CO ₂ to extinguish.
Unsuitable extinguishing media	Water jet spray
5.2 Special hazards arising from the substance or mixture	
	Flammable liquid and vapour. Decomposes in a fire giving off toxic fumes: Carbon monoxide, Carbon dioxide
5.3 Advice for firefighters	
	Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures	
	Provide adequate ventilation. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Wear suitable protective clothing, gloves and eye/face protection. Avoid breathing vapours. Wash hands and exposed skin thoroughly after handling.
6.2 Environmental precautions	
	Do not allow to enter drains, sewers or watercourses.
6.3 Methods and material for containment and cleaning up	
	Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal.
6.4 Reference to other sections	
	See Also Section 8, 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling	
	Avoid breathing vapours. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting/equipment. Use non-sparking tools. Take action to prevent static discharges. Wash hands and exposed skin thoroughly after handling. Avoid contact with skin and eyes.
7.2 Conditions for safe storage, including any incompatibilities	
	Store in a well-ventilated place. Keep cool.
Storage temperature	Ambient.
Storage life	Stable under normal conditions.
Incompatible materials	None known. Strong oxidising agents.
7.3 Specific end use(s)	
	Domestic, Commercial & Industrial use for concrete driveways, patios, paths & walkways, decorative, stamped, or pattern imprinted concrete.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters	
8.1.1 Occupational Exposure Limits	



Block Paving Sealant - Satin

Occupational Exposure Limits						
SUBSTANCE.	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Xylene, o-,m-,p- or mixed isomers	1330-20-7	50	220	100	441	Sk, BMGV
Methyl methacrylate	80-62-6	50	208	100	416	
Silica, amorphous inhalable dust	7631-86-9		6			
Silica, amorphous respirable dust	7631-86-9		2.4			

Region Source
 United Kingdom UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark Notes
 Sk Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.
 BMGV Biological monitoring guidance values are listed in Table 2.

Biological Exposure Indices						
Substances	CAS Number	Sampling	Tissues	Control parameters	Biological monitoring guidance value	Comments
Xylene, o-, m-, p- or mixed isomers	1330-20-7	650 mmol methyl hippuric acid/mol creatinine in urine	Post shift			

Remark Notes

8.2 Exposure controls

8.2.1. Appropriate engineering controls Ensure adequate ventilation.

8.2.2. Personal protection equipment



Eye Protection

Wear protective eye glasses for protection against liquid splashes.



Skin protection

Wear protective clothing and gloves: Impervious gloves (EN 374). Breakthrough time of the glove material: refer to the information provided by the gloves' producer.



Respiratory protection

Wear respiratory protection.



Thermal hazards

Not applicable.

8.2.3. Environmental Exposure Controls Do not allow to enter drains, sewers or watercourses.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance Liquid.
 Colour : Clear.
 Odour Characteristic odour.
 Odour threshold Not known.
 pH Not known.
 Melting point/freezing point -34°C
 Initial boiling point and boiling range Not known.
 Flash Point 30°C
 Evaporation rate Not known.

**Block Paving Sealant - Satin**

Flammability (solid, gas)	Not known.
Upper/lower flammability or explosive limits	Flammable Limits (Lower) (%v/v) : 1.1 Flammable Limits (Upper) (%v/v) : 7
Vapour pressure	0.866-0.870g/cm ³ @ 20°C
Vapour density	Not known.
Density (g/ml)	0.866-0.870g/cm ³ @ 20°C
Relative density	0.866-0.870g/cm ³ @ 20°C
Solubility(ies)	Solubility (Water) : Insoluble in water. Solubility (Other) : Not known.
Partition coefficient: n-octanol/water	Not known.
Auto-ignition temperature	500°C
Decomposition Temperature (°C)	Not known.
Viscosity	Not known.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2 Other information	None.

SECTION 10: STABILITY AND REACTIVITY**10.1 Reactivity**

Stable under normal conditions.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

Heat and direct sunlight.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on toxicological effects**

Acute toxicity - Ingestion	Calculation method : Not classified.
Acute toxicity - Skin Contact	Calculation method : Harmful in contact with skin. Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 1413.52000
Acute toxicity - Inhalation	Calculation method : Harmful if inhaled. Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 14.14000
Skin corrosion/irritation	Calculation method : Causes skin irritation.
Serious eye damage/irritation	Calculation method : Not classified.
Skin sensitization data	Calculation method : Not classified.
Respiratory sensitization data	Calculation method : Not classified.
Germ cell mutagenicity	Calculation method : Not classified.
Carcinogenicity	Calculation method : Not classified.
Reproductive toxicity	Calculation method : Not classified.
Lactation	Calculation method : Not classified.
STOT - single exposure	Calculation method : Not classified.
STOT - repeated exposure	Calculation method : Not classified.
Aspiration hazard	Calculation method : Not classified.

11.2 Other information

Not known.

SECTION 12: ECOLOGICAL INFORMATION**12.1 Toxicity**

Toxicity - Aquatic invertebrates	Low toxicity to invertebrates.
Toxicity - Fish	Low toxicity to fish.

**Block Paving Sealant - Satin**

Toxicity - Algae	Low toxicity to algae.
Toxicity - Sediment Compartment	Not classified.
Toxicity - Terrestrial Compartment	Not classified.
12.2 Persistence and degradability	Part of the components are biodegradable.
12.3 Bioaccumulative potential	No information on this formulation.
12.4 Mobility in soil	Insoluble in water. The product is predicted to have low mobility in soil.
12.5 Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6 Other adverse effects	Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods	Dispose of this material and its container as hazardous waste.
13.2 Additional Information	Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number	
UN No.	1263
14.2 UN proper shipping name	
UN proper shipping name	PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	
ADR/RID	
ADR/RID Class	3
ADR Classification Code	F1
Special Provisions	163 367 650
Limited Quantities	5 L
Excepted Quantities	E1
Emergency Action Code	•3Y
Mixed Packing Instructions for Packages	P001 IBC03 LP01 R001
Special Packing Provisions for Packages	PP1
Mixed Packing Instructions for Packages	MP19
Packing Instructions for Portable Tanks	T2
Special Provisions for Portable Tanks	TP1 TP29
Tank Code for Tanks	LGBF
Special Provisions for Tanks	
Vehicle for Tank Carriage	FL
ADR Transport Category	3
Tunnel Restriction Code	D/E
Special Provisions for Carriage - Packages	V12
Special Provisions for Carriage - Bulk	
Special Provisions for Carriage - Loading, Unloading and Handling	
Special Provisions for Carriage - Operation	S2
ADR HIN	30
IMDG	
IMDG Class	3
Special Provisions	163 367 650
Limited Quantities	5 L
Excepted Quantities	E1
Mixed Packing Instructions for Packages	P001 IBC03 LP01 R001
Special Packing Provisions for Packages	PP1
Packing Instructions for Portable Tanks	T2
Special Provisions for Portable Tanks	TP1 TP29
IMDG EMS	F-E, S-E
Stowage and Handling	Category A

**Block Paving Sealant - Satin**

Segregation

Marine Pollutant

ICAO/IATA

IATA Proper Shipping Name PAINT RELATED MATERIAL

Excepted Quantities E1

Passenger and Cargo Aircraft Limited Y344

Quantities Packing Instructions

Passenger and Cargo Aircraft Limited 10L

Quantities Max net Qty

Passenger and Cargo Aircraft Packing 355

Instructions

Passenger and Cargo Aircraft Max net 60L

Qty

Cargo Aircraft Packing Instructions 366

Cargo Aircraft Max net Qty 220L

Special Provisions A3, A72, A192

Emergency Response Guidebook (ERG) 3L

Code

Labels

Labels 3

**14.4 Packing group**

Packing group III

14.5 Environmental hazards

Environmental hazards Not classified as a Marine Pollutant.

14.6 Special precautions for user

Special precautions for user Not known.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No information available

SECTION 15: REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

United Kingdom Regulations - Authorisations and/or Restrictions On Use

UK REACH Candidate List of Substances Not listed

of Very High Concern for Authorisation

UK REACH Authorisation List (Annex Not listed

XIV) list of substances subject to
authorisation

UK REACH Restrictions List (Annex XIV) Xylene (1330-20-7), n-butyl methacrylate (97-88-1), methyl methacrylate (80-62-6)

Restrictions on the manufacture, placing

on the market and use of certain

dangerous substances, mixtures and

articles

The Persistent Organic Pollutants Not listed

Regulations 2007 (SI 2007/3106) as

amended

The Ozone-Depleting Substances and Not listed

Fluorinated Greenhouse Gases

(Amendment etc.) (EU Exit) Regulations

2019 (SI 2019/583)

The Prior Informed Consent (PIC) Not listed

Regulations concerning the export and

import of hazardous chemicals

SI2008/2108 as amended

European Regulations - Authorisations and/or Restrictions On Use

Community Rolling Action Plan (CoRAP) Xylene (1330-20-7), methyl methacrylate (80-62-6), silicon dioxide (7631-86-9)

15.2 Chemical Safety Assessment

United Kingdom A REACH chemical safety assessment has not been carried out.

SECTION 16: OTHER INFORMATION

**Block Paving Sealant - Satin**

The following sections contain revisions or new statements:

1-16

LEGEND

Hazard Pictogram(s)



GHS02



GHS07

Hazard classification

Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Acute Tox. 4 : Acute toxicity, Category 4
Skin Irrit. 2 : Skin corrosion/irritation, Category 2
Skin Sens. 1 : Skin sensitization, Category 1
Eye Irrit. 2 : Serious eye damage/irritation, Category 2
Acute Tox. 4 : Acute toxicity, Category 4
STOT SE 3 : Specific target organ toxicity — single exposure, Category 3

Hazard Statement(s)

H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.

Precautionary Statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P240: Ground and bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting/equipment.
P242: Use non-sparking tools.
P243: Take action to prevent static discharges.
P261: Avoid breathing vapours.
P264: Wash hands and exposed skin thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312: Call a POISON CENTER/doctor if you feel unwell.
P321: Specific treatment (see Medical Advice on this label).
P332+P313: If skin irritation occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P370+P378: In case of fire: Use water spray, foam, dry powder or CO₂ to extinguish.
P403+P235: Store in a well-ventilated place. Keep cool.
P501: Dispose of contents in accordance with local, state or national legislation.

Acronyms

ADN : European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road



Block Paving Sealant - Satin

ATE : Acute Toxicity Estimate
CAS : Chemical Abstracts Service
DNEL : Derived No Effect Level
EC : European Community
EINECS : European Inventory of Existing Commercial Chemical Substances
IATA : International Air Transport Association
IBC : Intermediate Bulk Container
ICAO : International Civil Aviation Organization
IMDG : International Maritime Dangerous Goods
LTEL : Long term exposure limit
PBT : Persistent, Bioaccumulative and Toxic
PNEC : Predicted No Effect Concentration
REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
RID : Regulations concerning the International Carriage of Dangerous Goods by Rail
STEL : Short term exposure limit
STOT : Specific Target Organ Toxicity
UN : United Nations
vPvB : very Persistent and very Bioaccumulative

Key literature references and sources for data used to compile the SDS
Disclaimers

GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Multicrete Products Limited gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Multicrete Products Limited accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.