

Frame	SPARK EVO, UHMS-EPS + Carbon, 12×142mm thru axle, Flat Mount Disc
Fork	SPARK EVO, HMS-HPT Carbon, 12×100mm thru axle, Flat Mount Disc
Shifter	Shimano 105 12 speed
Front derailleur	Shimano 105, 2×12 speed
Rear derailleur	Shimano 105 12 speed, Max 34T
Crank	Shimano 105, 50-34T
Cassette	Shimano 105, 11-34T, 12 speed
Chain	Shimano CN-M8100 QUICK-LINK
Bottom Bracket	BB30RL PF30
Brake	Shimano 105 Hydraulic Disc Brake
Rotor	Shimano RT800, Center Lock, F160mm, R140mm
Front wheel	MVMT Bronze R50, Carbon Tubeless Ready, Center Lock, 100×12mm thru axle
Rear wheel	MVMT Bronze R50, Carbon Tubeless Ready, Center Lock, Shimano HG, 142×12mm thru axle
Tire	'MICHELIN Power Cup Tubeless Ready 700X28C
Handlebars	MVMT A-TYPE Carbon, Integrated Handlebar, 60mm reach, 130mm drop
Stem	-
Seat Post	PARDUS SPARK EVO, Carbon, 0mm offset, 350mm, Di2-compatible
Saddle	Selle Italia MODEL X Superflow

** Specifications are subject to change without notice*