

fuvelo : Specification Sheet

Frame	SPARK SPORT, HS-EPS+ Carbon Fiber, 12×142mm Thru-Axle, Flat Mount Disc Brake
Fork	SPARK SPORT, HS-HPT Carbon Fiber, 12×100mm Thru-Axle, Flat Mount Disc Brake, Offset 50mm (XXS/XS), Offset 45mm (S/M/L/XL)
Shifters	LWOO eR9 12 speed
Front derailleur	LWOO eR9, 2×12 speed
Rear derailleur	LWOO eR9 12 speed, Max 34T
Crank	Senicx crank
Cassette	LWOO eR9, 11-30T, 12 speed
Chain	Shimano CN-M8100 QUICK-LINK
Bottom Bracket	BB30RL PF30
Brake	LWOO eR9 Hydraulic Disc Brake
Rotor	Shimano RT800, Center Lock, F160mm, R140mm
Front wheel	MVMT Bronze R50, Carbon Tubeless Ready, Center Lock, 100×12mm thru axle
Rear wheel	MVMT Bronze R50, Carbon Tubeless Ready, Center Lock, Shimano HG, 142×12mm thru axle
Tire	Chaoyang 700X28C
Handlebars	MVMT A-TYPE Carbon, Integrated Handlebar, 60mm reach, 130mm drop
Stem	—
Seat Post	PARDUS SPARK EVO, Carbon, 0mm offset, 350mm, Di2-compatible
Saddle	MVMT M-Gold Full Carbon

Specifications are subject to change without notice