

# SIRRUS X 1.0 STEP-THROUGH

GBP75.00



STN REFL DPMRNBLU GRYBLU

Offering an unprecedented combination of comfort, efficiency, and nimble handling, the Sirrus X excels on pavement, dirt, and any terrain in between.

- Lightweight A1 Alloy frame with clean internal cable routing, 3.5lbs (1.7kg).
- Maximum control through intuitive shifting with 1x7 wide range gearing.
- Float over rough terrain with fast rolling Specialized Pathfinder 42c tires featuring proprietary Gripton rubber compound.

SIRRUS X 1.0 STEP-THROUGH	XS	S	M
Stack (mm)	555	563	593
Reach (mm)	393	400	408
Head-Tube Length (mm)	139	147	175
Head-Tube Angle (degrees)	70	70	71
B-B Height (mm)	288	288	288
B-B Drop (mm)	70	70	70
Trail (mm)	76	76	69
Fork Length (full) (mm)	395	395	395
Fork Rake/Offset (mm)	51	51	51
Front-Center (mm)	628	637	646
Chain-Stay Length (mm)	440	440	440
Wheelbase (mm)	1058	1068	1077
Top-Tube Length (horizontal) (mm)	557	567	584
Bike Stand-Over Height (mm)	636	636	641
Seat-Tube Length (mm)	395	450	500
Seat-Tube Angle (degrees)	73.5	73.5	73.5
Crank Length (mm)	165	165	170
Handlebar Width (mm)	660	660	660
Stem Length (mm)	60	60	75
Saddle Width (mm)	155	155	143
Seatpost Length (mm)	300	300	350

## SPECS

### Specifications subject to change without notice.

FRAME	Specialized A1 Premium Aluminum, Fitness Geometry, butted tubing, internal cable routing, flat-mount disc, quick-release, Plug + Play rack/fender mounts
FORK	Hi-Ten steel, flat-mount disc, Plug + Play fender mounts, low rider rack mounts, quick-release
HANDLEBARS	Double-buttressed alloy, 5-degree backsweep, 25.4mm
STEM	Alloy, 25.4mm, 10deg.
SADDLE	Bridge Sport, Steel rails, 155/143mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm
SEAT BINDER	Bolt-type, 31.8mm
FRONT BRAKE	Tektro MD-U310R, Mechanical Disc
REAR BRAKE	Tektro MD-U310R, Mechanical Disc
CHAIN	
CRANKSET	PROWHEEL, Alloy, 165mm
CHAINRINGS	40T
BOTTOM BRACKET	Square-tapered, 68mm
REAR DERAILLEUR	Shimano Acera RD-M3020, 7-Speed
SHIFT LEVERS	Shimano Altus SL-M315-7R, 7-Speed
CASSETTE	microSHIFT CS-H074, 12-40t, 7-Speed
RIMS	700c disc brake, double-wall alloy, 22mm depth, 21mm internal width
FRONT HUB	Alloy, 6-bolt disc, loose ball bearing, quick-release, 32h
REAR HUB	Alloy, 6-bolt disc, 8/9-Speed freehub, loose ball bearing, quick-release, 36h, 10x135mm
SPOKES	Stainless, 14g
FRONT TYRE	Pathfinder Sport, 700x42
REAR TYRE	Pathfinder Sport, 700x42
INNER TUBES	Standard 40mm SV 700x32-50
PEDALS	Specialized, platform

PART NO.	DESCRIPTION	COLOUR	SIZE
92425-9201	SIRRUS X 1.0 ST DPMRNBLU/GRYBLU XS	STN REFL DPMRNBLU GRYBLU	XS
92425-9202			S
92425-9203			M