

# LEVO R EXPERT NB

GBP,499.00



GLOSS CARBON / BURNT GOLD METALLIC



SATIN PISTACHIO / DARK MOSS GREEN

Nothing this powerful has ever felt this agile. Light, tight, and ready to fight, Levo R channels the SuperNatural power of Levo 4 but sheds its manners. Like a rally car unleashed on dirt, you and Levo R become one, stealing endless flow and finishing with the grin of a thief who slipped away clean. This is Electric Rally

- Use - Full Power Electric Rally
- E-System - Specialized 3.1 Motor w/ 810 Watts & 105 Nm, 840 Wh Battery, up to 5 hour range
- Frame - FACT 11m Carbon, Geo Adj & SWAT Storage
- Suspension - Front: 140mm FOX 36 SL Performance Elite GRIP X Rear: 130mm GENIE - FOX FLOAT Performance Elite
- Drivetrain - SRAM GX Transmission
- Wheels - Travesse SL2 w/ I9 1/1 Hubs

LEVO R EXPERT NB	S1	S2	S3	S4	S5	S6
Stack (mm)	602	607	616	630	644	657
Reach (mm)	400	420	450	475	500	525
Head-Tube Length (mm)	95	100	110	125	140	155
Head-Tube Angle (degrees)	64.8	65	65	65	65	65
B-B Height (low) (mm)	339	339	339	339	339	339
B-B Drop (mm)	36	36	36	36	36	36
Trail (mm)	128	126	126	126	126	126
Fork Length (full) (mm)	550	550	550	550	550	550
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	716	736	770	801	833	863
Chain-Stay length (mm)	447	447	447	447	447	447
Wheelbase (mm)	1160	1181	1215	1246	1277	1309
Top-Tube Length (horizontal) (mm)	539	560	592	620	649	677
Bike Stand-Over Height (mm)	761	763	773	783	793	803
Seat-Tube Length (mm)	375	385	405	425	445	465
Seat-Tube Angle (degrees)	77	77	77	77	77	77
Seat Post Max Insertion (mm)	210	227	249	271	292	312
Seat Post Min Insertion (mm)	80	80	80	80	80	80
Saddle Height for Effective ST Angle (mm)	645	690	735	780	825	870

## SPECS

## Specifications subject to change without notice.

FRAME	FACT 11m Carbon, SWAT downtube storage, 12x148mm UDH compatible rear dropout, side entry battery, adjustable geometry, 130mm of travel
SEAT BINDER	Alloy, 38.6mm
FORK	FOX 36 SL Performance Elite, GRIP X Damper, HSC, LSC, LSR adjust, 140mm travel, 44mm offset, 15x110mm
REAR SHOCK	FOX FLOAT Performance Elite GENIE, Ride Dynamics Developed, 2-position compression adjust, 190x45mm
HANDLEBARS	Specialized Alloy, 30mm/40mm rise, 35mm, 800mm wide
STEM	Alloy Trail Stem, 35mm bar bore
GRIPS	Specialized Trail Grips
SADDLE	Body Geometry Power Comp, steel rails
SEATPOST	X-Fusion Manic, 34.9, S1-S2: 125mm, S3: 150mm, S4: 170mm, S5-S6: 190mm Travel, 0mm offset
FRONT BRAKE	SRAM Motive Bronze, 4-piston caliper, hydraulic disc, 200mm rotor
REAR BRAKE	SRAM Motive Bronze, 4-piston caliper, hydraulic disc, 200mm rotor
CHAIN	SRAM GX Eagle Transmission 12-Speed Flattop Chain
CRANKSET	SRAM GX Alloy Crank, ISIS interface, 55mm chainline, 160mm
CHAINRINGS	SRAM 34t T-Type chainring, 104 BCD, steel
REAR DERAILLEUR	SRAM GX Eagle AXS Transmission
SHIFT LEVERS	SRAM AXS POD Controller
CASSETTE	SRAM GX Transmission, XS 1275, 10-52t
FRONT WHEEL	Roval Traverse SL II Rim, hookless carbon, 30mm inner width, tubeless ready, 29", Industry 9 1/1 Hub, 15x110mm, 28H, Sapim D-Light Spokes
REAR WHEEL	Roval Traverse SL II Rim, hookless carbon, 30mm inner width, tubeless ready, 29", Industry 9 1/1 Hub, 12x148mm, 32H, Sapim D-Light Spokes
INNER TUBES	Standard, Presta Valve
MOTOR	Specialized 3.1 Motor, 101Nm torque, 666W power
UI/REMOTE	Mastermind TCU, 2.2" high resolution screen, fully customizable with Specialized app, works with Apple Find My
BATTERY	840Wh battery
CHARGER	Specialized 4amp charger
SWAT	SWAT internal downtube storage

PART NO.	DESCRIPTION	COLOUR	SIZE
95226-3302	LEVO R EXPERT NB CARB/BNTGLDMET S2 - 29	GLOSS CARBON / BURNT GOLD META	null
95226-3303			null
95226-3304			null
95226-3305			null
95226-3306			null
95226-3202	LEVO R EXPERT NB PST/DK MOS S2 - 29	SATIN PISTACHIO / DARK MOSS GR	null
95226-3203			null
95226-3204			null
95226-3205			null
95226-3206			null